Legend 880/Tasword II Instructions

Copyright 1985 by E. Arthur Brown Company

To set up your legend 880 for Tasword II Word Processing, first remember that Tasword II has the printer driver software already in it, so you mustn't load the Tasman Centronics Interface software tape. Before powering up, be sure your Tasman interface is firmly connected to your computer and it's cable is firmly connected to your legend 880. Power up everything and load Tasword II by typing LOAD "" (ENTER) and pressing the PLAY button of your recorder. Once the program is loaded, hold down the symbol shift key and press STOP. A menu will appear. Press the "g" selection and (ENTER). You will be presented with a display that's similar, but different from the one below. Change it to match the one below and you will configure Tasword II to use the special features of your Legend 880 printer.

```
Tasword Two-2068 Microdrive
      © Tasman Software 1983
Printer control graphics chars:

128      27   80   0
    129  27   87   0
130      18
    131  27   45   0
132      53
    133  27   70
134      27   84   27   72
    135  27   84   27   72
136      27   83
    137  27   84   1
138      27   84   0
    139  27   45
140      27   45   1
    141  15
142      27   87   1
    143  12
```

On	Legend 880	Off	Key
	Enlarged		1
	Condensed		2
	Underlined		3
	Italic		4
	Emphasized		5
	Superscript		6
	Subscript		7
	Form Feed		8

↑— CODE CHANGES

MENU CHANGES ———————→

Next, use the instructions from your Tasword II tip sheet to modify the help menu to show the changes in functions you've made so you'll have those references on screen when using Tasword II.

Finally, a tip for using the Tasman Centronics Interface for making High Resolution Screen copies with your Legend 880: LOAD "tas-shinwa" CODE for the interface. The command RANDOMIZE USR 23296 will give a screen copy the full width of your paper. If you want a small screen copy, use the command POKE 23548,1 before using the RANDOMIZE USR 23296 command. Incidently, the tas-shinwa program is on the interface tape.